

Q1® Spray Overall

Q1® Spray Overall provides optimal personal protection against overspray, solvents and dust during spray painting jobs in the booth. Made of anti-static polyester, Q1® coverall is designed to be light, resistant and breathable, ensuring a high level of comfort and freedom of movement during the use. Moreover, it is completely washable and provides long lasting usage. Elastic arm cuffs, adjustable waist band and Velcro closure on the legs allow a secure and adjustable fit when wearing.



Features

- 100% Polyester
- Lint & Silicon free
- Antistatic coating

Benefits

- Completely washable and reusable
- Light and breathable for high comfort
- Adjustable and safe fit

Available Colour

Dark grey & yellow

Product Reference

Part#	Size	Pcs/ Case
SPO_S	Small	75 suits/ box
SPO_M	Medium	75 suits/ box
SPO_L	Large	75 suits/ box
SPO_XL	Extra Large	75 suits/ box
SPO_2XL	2x Extra Large	75 suits/ box
SPO_3XL	3x Extra Large	75 suits/ box

Technical Data Sheet

Characteristics

Material: Polyester

CE Certification

Lint and Silicon free

Antistatic EN1149-5

PSA Cat.1

Washable till 40° recommended before first use



Additional Information**Storage & Handling**

Q1® Premium Masking Solutions must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 59°F / 15°C to 77°F / 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

Shelf life from date of manufacture

No yellowing and < 10% loss in performance at 73.4°F / 23 °C, 50% humidity is considered 12 months Q1® Premium Masking Solutions does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1® Premium Masking Solutions believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1® Premium Masking Solutions has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Product Use

Q1® would advise that there are many factors beyond Q1®' control but within the users knowledge that can affect the use and performance of Q1® products. Q1® remind the user of the products to make sure that its range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1® literature.